

AG Series Dual-channel Arbitrary Waveform Generator



- + Advanced DDS technology, max 60MHz frequency output
- + Up to 250MS/s sample rate, and 1μHz frequency resolution
- + Vertical Resolution : 14 bits, up to 1M arb waveform length
- + Comprehensive waveform output : 5 basic waveforms, and 48 built-in arbitrary waveforms
- + Comprehensive modulation functions : AM, FM, PM, FSK, PWM, Sweep, and Burst
- + High-accuracy frequency counter integrated, supported range 100mHz - 200MHz
- + Supported SCPI
- + 4 inch high resolution (480 × 320 pixels) TFT LCD display

+ Performance Specifications

Model	AG1012	AG1012F	AG1022	AG1022F	AG2052F ^{NEW!}	AG2062F ^{NEW!}
Channel	dual					
Frequency Output	10MHz		25MHz		50MHz	60MHz
Sample Rate	125MS/s			250MS/s		
Vertical Resolution	14 bits					

Waveform

Standard Waveform	Sine, Square, Pulse, Ramp, and Noise
Arbitrary Waveform	Exponential Rise, Exponential Fall, Sin(x)/x, Step Wave, and others, total 48 built-in waveforms, and user-defined arbitrary waveform

Frequency (resolution 1μHz)

Sine	1μHz - 10MHz	1μHz - 25MHz	1μHz - 50MHz	1μHz - 60MHz
Square	1μHz - 5MHz		1μHz - 25MHz	1μHz - 30MHz
Pulse	1μHz - 5MHz		1μHz - 10MHz	
Ramp	1μHz - 1MHz			
Noise	25MHz (-3dB) (typical)			
Arbitrary Waveform	1μHz - 10MHz			

Amplitude

Amplitude	1m Vpp - 10 Vpp (50Ω), 1m Vpp - 20 Vpp (high impedance)
Resolution	1m Vpp or 14 bits
DC Offset Range (AD+DC)	±5V (50Ω), ±10V (high impedance)
DC Offset Range Resolution	1mV
Load Impedance	50Ω (typical)

Model	AG1012	AG1022	AG1012F	AG1022F	AG2052F ^{NEW!}	AG2062F ^{NEW!}
-------	--------	--------	---------	---------	-------------------------	-------------------------

Arbitrary Waveform

Wave Length	2 pts to 8K pts			2 pts to 1M pts		
Non-volatile Memory	26 waveforms					

Modulation

Modulation Waveform	/	AM, FM, PM, FSK, Sweep, and Burst	AM, FM, PM, FSK, PWM, Sweep, and Burst
Modulation Frequency	/	2mHz to 20.00KHz (FSK 1μHz - 100KHz)	

Counter

Function	/	Frequency Period, +Width, -Width, +Duty, and -Duty	
Frequency Range	/	100mHz - 200MHz	
Frequency Resolution	/	6 digits	

Power Amplifier Specification (Optional)

Bandwidth	DC-100kHz		
MaxOutputPower	10W		
Gain	X10		
Max Output Voltage	22Vpp		

Input / Output

Display	4 inch (480 × 320 pixels) TFT LCD		
Type	external reference clock input / output	counter external modulation input / output, external trigger input / output, external reference clock input / output	
Communication Interface	USB host, USB device, RS232		

Mechanical

Dimension (W×H×D)	235 × 110 × 295 (mm)		
Weight (without package)	3.00 kg		

Specifications subject to change without prior notice.

+ Application

design and debug circuit function test education and training

+ Accessories

The accessories subject to final delivery.



Power Cord



CD Rom



Manual



USB Cable



Q9