

WiFi temperature and relative humidity sensor for 4 external probes

code: W3745



Sensors with WiFi interface are designed to measure temperature and relative humidity from connected probe (optional accessories) and to measure the temperature from up to 3 connected Pt1000 probes (optional accessories).

Communication with the sensor is done via a wireless WiFi network. The device allows sending measured values to the online [COMET Cloud](#) (with the shortest interval of 5 minutes) or into [COMET Database](#). The values can be displayed on integrated web pages and provided to third party systems using the Modbus TCP, SNMP, JSON and XML. The measured values are displayed on the LCD display.

The device continuously evaluates the alarm limits of the measured values and in case of exceeding them, it can send an e-mail or inform by means of acoustic or optical signaling. Two alarm limits are supported for each measurement channel.

The main advantage of sensors with WiFi interface is the simplicity of deployment in places where WiFi infrastructure is already available. Just place the sensor in the desired location and connect it to the WiFi network. WiFi sensor in conjunction with [COMET Cloud](#) offers a comprehensive solution for monitoring and alarm without the need for a server solution on the part of the user. If necessary, however, the sensor can also be connected to third-party systems, either using the Modbus TCP protocol, SNMP protocol or by sending JSON data to an http server. Sensor allow to provide values via XML and JSON using HTTP GET requests as well.

Thanks to these unique features, the WiFi sensor will find applications and a wide range of application areas.

With a newly purchased WiFi sensor, you receive 3 months of [COMET Cloud](#) for free; a full year of operation in [COMET Cloud](#) then requires [1 credit](#).

Technical data

TEMPERATURE SENSOR	
Measuring range	according to the connected probe Digi/E
Accuracy	according to the connected probe Digi/E
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	according to the connected probe Digi/E
Accuracy	according to the connected probe Digi/E
Resolution	0.1% RH
TEMPERATURE SENSOR - external probe Pt1000	
Measuring range	-90 to +260 °C (optionally -150 to +600°C)

Accuracy	$\pm 0.2\text{ }^{\circ}\text{C}$ in the range -90 to +100 $^{\circ}\text{C}$; $\pm 0.2\text{ }%$ from reading from +100 to +260 $^{\circ}\text{C}$
Resolution	0.1 $^{\circ}\text{C}$
DEW POINT	.
Measuring range	according to the connected probe Digi/E
Accuracy	according to the connected probe Digi/E
Resolution	0.1 $^{\circ}\text{C}$
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +60 $^{\circ}\text{C}$
Channels	1x connectable temperature+humidity probe (ELKA connector); 3x connectable Pt1000 temperature probe (CINCH conektor)
Measuring interval	1 s
Sending interval to COMET Cloud	adjustable 5 minutes to 12 hours
Communication protocols	HTTP(S), SMTP, ModbusTCP, SNMP (v1, v2c, v3), HTTP POST, HTTP GET (JSON, XML)
Alarm signalization	e-mail, acoustic, LED
Power	5.0 to 5.4 VDC; consumption 150 mA (max. 500 mA); USB-C connector
Radio section	frequency: 2.4 GHz; max. transmit power: 18 dBm; standard: IEEE 802.11 b/g/n
WiFi security	Open, WEP, WPA, WPA2, WPA2-PMF, WPA3, WPA2-EAP
Protection class	IP30
Dimensions	133 x 93 x 32 mm
Weight	117 g
Warranty	3 years