




Ecoclick Starters



Dimensions (mm)

C	E
max.	max.
40.3	21.5

Product Description

- Range of premium-quality glow switch starters for igniting fluorescent lamps with electromagnetic ballast.

Product Features

- Redesigned canister top with 2 installation notches into which the pins of another starter fit perfectly (patented innovation)
- Radioactive-free (patented) and lead-free (RoHS-compliant)
- Premium reliability with 10,000 safe switches
- 2-pin igniter in plastic (flame-retardant polycarbonate) canister with high-quality radio-interference suppression capacitor
- Well-defined preheat and peak voltage ensure proper ignition

Product Benefits

- The only starter that offers fast, easy installation with no need to use any extra tools

- No irritation – even firmly stuck starters can be removed easily
- Eco-friendly, recyclable concept (free of lead and radioactivity)
- More than 25% longer lamp life; lower maintenance costs compared with lower-quality, non-IEC-compliant starters
- Optimal connectivity through brass components and oxidation-resistant brass pins
- Flame-retardant components and UV-resistant canister for additional safety and secure ignition (validated by Underwriters Laboratories UL)

Application

- Ignite fluorescent lamps of all brands with conventional electromagnetic ballast using TL-D (T8), TL (T12), TL mini and PL-L lamps
- S2 Ecoclick starters are suitable for:

- 110/130V, 4-22W single applications
- 220/240V, 4-6-8-15-18-22W single applications
- 220/240V, 4-22W series applications

- S10 Ecoclick starters are suitable for 220/240V, 4-65W single applications
- S10 Ecoclick starter is required for 220/240V, 13W single application
- S2 Ecoclick starter is recommended for 220/240V, 18W single application for optimum performance

System

- Starter replacement recommended when replacing fluorescent lamps

Type	Wattage	System Description	Voltage	Bulb finish	Add. Info.	Packing type	Packing configuration	Colour of the Housing	Photo letter	Ordering number
S10	4-65W	SIN	220-240V	WH		UNP	1000	White	A	8711500... 697691 28
S2	4-22W	SER	220-240V	WH		UNP	1000	White	B	697509 28
S2	4-22W	SER	220-240V	WH	EUR	1NO	20X10CT	White	B	697509 31
S10	4-65W	SIN	220-240V	WH		1NO	20X10CT	White	A	697691 31

4-20090109

Ecoclick Starters

Additional technical data

Product name	System Description	Ambient Temperature min. (°C)	Ambient Temperature max. (°C)	Capacitor	Pulse Voltage min. (V)	Non Reclosure Voltage min. (V)
S10 4-65W SIN 220-240V WH	Single	-15	75	yes	900	140
S2 4-22W SER 220-240V WH	Series	-15	75	yes	800	70

Logistic data

Product name	National Order Code	Packing type	Packing type description	Packs per outer box	Packing configuration
S10 4-65W SIN 220-240V WH	S101000W	UNP	Unpacked	1000	1000
S2 4-22W SER 220-240V WH	S21000W	UNP	Unpacked	1000	1000
S2 4-22W SER 220-240V WH EUR	S210W	1NO	-	200	20X10CT
S10 4-65W SIN 220-240V WH	S1010W	1NO	-	200	20X10CT

Product name	Quantity per pack	Packing length (mm)	Packing width (mm)	Packing height (mm)	Gross weight per piece (g)	Net weight per piece (g)
S10 4-65W SIN 220-240V WH	1	400	300	193	7.38	7
S2 4-22W SER 220-240V WH	1	400	300	193	7.74	7
S2 4-22W SER 220-240V WH EUR	1	225	225	85	8.30	7
S10 4-65W SIN 220-240V WH	1	225	225	85	8.30	7

Additional extended technical data

Product name	Name Extension	Execution	Cap-Base Information
S10 4-65W SIN 220-240V WH	S10	White	2P
S2 4-22W SER 220-240V WH	S2	White	2P