


MECHANICAL DATA

- * Case: Metal, electrically isolated
- * Epoxy: UL 94V-0 rate flame retardant
- * Terminals: Plated .25"(6.35mm) Faston lugs, solderable per MIL-STD-202E, Method 208 guaranteed
- * Polarity: As marked
- * Mounting position: Any
- * Weight: 30 grams

FEATURES

- * Metal case for Maximum Heat Dissipation
- * Surge overload ratings-400 Amperes
- * Low forward voltage drop



MB-25



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%.

PARAMETER	SYMBOL	KBPC35005 MB3505	KBPC3501 MB351	KBPC3502 MB352	KBPC3504 MB354	KBPC3506 MB356	KBPC3508 MB358	KBPC3510 MB3510	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Bridge Input Voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current at $T_c = 55$	I_o				25				Amps
Peak Forward Surge Current 8.3 ms single half sine-wave Superimposed on rated load (JEDEC Method)	I_{FSM}				400				Amps
Maximum Forward Voltage Drop per element at 17.5A DC	V_F				1.1				Volts
Maximum DC Reverse Current at $@T_A = 25$ Rated DC Blocking Voltage	I_R				10				uAmps
I^2t Rating for Fusing ($t < 8.3ms$)	I^2t				500				
Typical Junction Capacitance (Note 1)	C_J				664				μF
Typical Thermal Resistance (Note 2)	R_{Jc}				300				mW
Operating and Storage Temperature Range	T_J, T_{STG}				2.2				
					-55 to +150				

Notes: 1. Measured at 1 MHz and applied reverse voltage of 4.0 volts

2. Thermal Resistance from Junction to Case per legs.

RATING AND CHARACTERISTIC CURVES

