

VDS Series PC Oscilloscope



- + Up to 100MHz bandwidth, and max 1GS/s real-time sample rate
- + 2 / 4 channels
- + Max 10M record length
- + Friendly UI : FFT, or X-Y, and waveform 2 views displayed on the same screen
- + Multi-trigger option : edge, video, slope, pulse, and alternate
- + USB isolation - less signal inference, more PC protection
- + USB bus powering, and LAN remote control (optional)
- + Ultra-thin body design, easy portability

Performance Specifications

Model	VDS1022I	VDS1022	VDS2062	VDS2064	VDS3102	VDS3104
Bandwidth	25MHz		60MHz		100MHz	
Channel	2+1 (multi)		4+1 (multi)		2+1 (multi)	4+1 (multi)
Sample Rate	100MS/s		500MS/s		1GS/s	
Horizontal Scale (s/div)	5ns/div - 100s/div, step by 1 - 2 - 5			2ns/div - 100s/div, step by 1 - 2 - 5		
Rise Time	≤14ns		≤5.8ns		≤3.5ns	
Record Length	5K		10M	5M	10M	5M
Input Coupling	DC, AC, GND					
Input Impedance	1MΩ ± 2%, in parallel with 10pF ± 5pF					
Channels Isolation	50Hz : 100 : 1 ; 10MHz : 40 : 1					
Max Input Voltage	400V (PK - PK) (DC + AC, PK - PK)		40V (PK - PK) (DC + AC, PK - PK)			
DC Gain Accuracy	±3%					
DC Accuracy	Average ≥ 16 : ±(3% reading + 0.05 div) for △T					
Probe Attenuation Factor	1X, 10X, 100X, 1000X					
LF Respond (AC, -3dB)	≥5Hz (at input, AC coupling, -3dB)					
Sampling Rate / Relay Time Accuracy	150ps					
Interpolation	sin(x)/x					
Interval (△T) Accuracy (full bandwidth)	Single : ± (1 interval time + 100ppm × reading + 0.6ns), Average > 16 : ±(1 interval time + 100ppm × reading + 0.4ns)					
Vertical Resolution (A/D)	8 bits (2 channels simultaneously)					

Model	VDS1022I	VDS1022	VDS2062	VDS3102	VDS2064	VDS3104
Vertical Sensitivity				5mV/div - 5V/div		
Trigger Type			Edge, Pulse, Video, Slope, Alternate			
Trigger Mode			Auto, Normal, Single			
Trigger Level			±5 divisions from screen center			
Acquisition Mode			Sample, Peak Detect, and Average			
Line / Field Frequency (video)			NTSC, PAL, and SECAM standard			
Cursor Measurement			△V, and △T between cursors			
Automatic Measurement			Vpp, Vavg, Vrms, Freq, Period, Vmax, Vmin, Vtop, Vbase, Vamp, Overshoot, Preshoot, Rise Time, Fall Time, Delay A→B, Delay A→B, +Width, -Width, +Duty, -Duty			
Waveform Math			+, -, ×, ÷, invert, FFT			
Lissajous Figure	Bandwidth		full bandwidth			
	Phase Difference		±3 degrees			
Communication Interface	USB2.0 (isolation)	USB2.0		USB2.0, LAN (optional)		
Multi-function Interface	Signal Type		synchronized input / output, Pass / Fail, external trigger input			
	Level Standard		TTL			
Power Supply			5.0V/1A			
Power Consumption		≤1.5W		≤5W		
Dimensions (W × H × D)		170 × 120 × 18 (mm)		190 × 120 × 18 (mm)		
Weight (without package)		0.26 kg		0.30 kg		

Specifications subject to change without prior notice.

Application

design and debug circuit function test education and training

Accessories

The accessories subject to final delivery.



Probe Probe Adjust Power Cord* CD Rom Manual USB Cable Adapter* Silicon Gel Case

* Power cord and adapter only available for models with LAN port.